



TECNO-S 240

Technical information

TECNO-S 240 is Marvon's a single-component acrylic sealant designed and developed to ensure the fire resistance up to EI 240 of penetration and linear joint seals on wall and floor according to EN 1366-3 and EN 1366-4.

Application field

TECNO-S 240 can be used on:

- Flexible wall (plasterboard).
- Rigid wall (masonry, concrete and aerated concrete).
- Timber wall.
- Rigid floor (concrete or aerated concrete).
- Timber floor.

It has a fire resistance up to EI 240 classified according to EN 13501-2 for:

- Combustible pipes (PVC-U, PVC-C, PE, LDPE, MDPE, HDPE, ABS, SAN+PVC, PP).
- Combustible soundproof pipes (e.g. Valsir Triplus[®], Valsir Silere[®], Valsir PP3, Valsir Blackfire[®]).
- Multilayer pipes.
- Incombustible pipes.
- Single or bundled electrical cables and corrugated pipes.
- Empty holes.
- Linear joint and gap seals.

Technical data

Fire resistance	Up to EI 240
Fire reaction	D-s1, d1
Characteristics	Single-component acrylic sealant
Weight	550 g/pcs
Expansion in fire	1:2/3
Application temperature	5°C - 30°C
Colour	White
Airborne sound insulation	$R_w (C; C_{tr}) = 62 (-1; 5)$ dB
Content, emission and/or release of dangerous substances	IA1, S/W3
Storage	18 months (in normal conditions)
Working life	30 years
TVOC	< 0.5 mg/m ² h
Durability	Z ₂ : use for internal conditions (relative humidity between 50% - 85% and temperature not below 0°C)
AVCP system	1

Dimensions



COD.

MA0TF505002

ml

310

Packaging

310 ml cartridges in cardboard boxes with 25 items.

Standard rules

- Test Standard: EN 1366-3 - EN 1366-4.
- Fire Classification Standard: EN 13501-2.
- European Assessment Document: EAD 350454-00-1104 - ETAG 026-3.

Certifications

- European Technical Assessment: ETA 22/0431 - ETA 22/0441.

Technical specification

Supply and installation of acrylic sealant TECNO-S 240 certified according to ETA 22/0431 and ETA 22/0441 for fire protection up to EI 240 of combustible pipes, multilayer pipes, incombustible pipes, single and bundled electrical cables, corrugated pipes, empty holes and linear joint and gap seals on wall and floor.

The sealant must be applied with appropriate gun.

For different applications please refer to European Technical Assessment.

310 ml cartridges.



Marvon S.r.l. - Società a socio unico
Via Gargnà 6 - 25078 - Vestone (BS) ITALY
Telefono: +39 0365 81.390 - Fax: +39 0365 879.923
e-mail: marvon@marvon.com - www.marvon.com

Soggetta all'attività di direzione e coordinamento ex art. 2497 bis C.C.
da parte di Silmar Group S.p.A. - Codice Fiscale 02075160172

