



## TECNOBRICK

### Technical information

TECNOBRICK is Marvon's polyurethane sponge intumescent brick designed and developed to ensure fire resistance up to EI 180 of penetration seals on wall and floor according to EN 1366-3.

TECNOBRICK is an easily shaped spongy product suitable to seal holes in different geometries.

When exposed to fire, it expands at 200°C further increasing its volume thanks to the presence of graphite.

### Application field

TECNOBRICK can be used on:

- Flexible wall (plasterboard).
- Rigid wall (masonry, concrete or aerated concrete).
- Rigid floor (concrete or aerated concrete).

It has a fire resistance up to EI 180 to classified according to EN 13501-2 for:


- Combustible pipes (PVC-U, PVC-C).
- Multilayer pipes.
- Insulated incombustible pipes (copper or steel).
- Cable trays and corrugated pipes.
- Empty holes.

**N.B.** The brick is used in case of large crossing and penetration of mixed services. Seal any remaining gap with TECNOGRAPHIT foam.

## Technical data

<b>Fire resistance</b>	Up to EI 180
<b>Fire reaction</b>	Performance not assessed
<b>Dimensions</b>	150x150x50 mm
<b>Weight</b>	220 g/pcs
<b>Density</b>	240 ±10% kg/m <sup>3</sup>
<b>Thermal conductivity</b>	0.062 W/mK
<b>Installation temperature</b>	5°C - 35°C
<b>Colour</b>	Dark grey
<b>Storage</b>	Unlimited (under normal conditions)

## Dimensions



<b>COD.</b>	<b>LxH</b>	<b>s</b>
MA0TF500300	150x150	50

All the dimensions are in mm.

## Packaging

- 12 items for cardboard box.

## Standard rules

- Test Standard: EN 1366-3.
- Fire Classification Standard: EN 13501-2.

## Certifications

- European Technical Assessment: ETA 21/0580.

## Technical specification

Supply and installation of polyurethane sponge intumescent brick TECNOBRICK certified in accordance to EN 1366-3, for fire protection up to EI 180 of combustible pipes, multilayer pipes, incombustible pipes, cable trays, corrugated pipes, mixed services, empty holes and ventilation ducts on wall and floor.

The brick is used in case of large crossing and penetration of mixed services.

Seal any remaining gap with TECNOGRAPHIT foam.

For different applications please refer to European Technical Assessment (ETA).

Brick dimensions 150x150x50 mm.



**Marvon S.r.l.** - Società a socio unico  
Via Gargnà 6 - 25078 - Vestone (BS) ITALY  
Telefono: +39 0365 81.390 - Fax: +39 0365 879.923  
e-mail: [marvon@marvon.com](mailto:marvon@marvon.com) - [www.marvon.com](http://www.marvon.com)

Soggetta all'attività di direzione e coordinamento ex art. 2497 bis C.C.  
da parte di Silmar Group S.p.A. - Codice Fiscale 02075160172

